

Quick Connect 2 dispense head

No drops, 100% tight



Properties

- Suitable with all Quick Connect 2 Adapters.
- Available in vertical and horizontal versions for various installation conditions
- Up to **25l/min** flow rate
- No risk of wrong chemical thanks to pin-to-hole concept (coding)
- High Purity products made of PE/PP/CD/PVDF assembled in clean room environment
- **Also conductive** for flammable liquids
- Venting port for pressure equalization
- Safe conversion between liquid and venting ports as well as between dispensing and filling functions thanks to the modular system

Example Specification:

DH-**X**X-**XX**-**XXX**-**XF**X/**X**-**XF**X/**X**

DH	Dispense Head
X	Function D = Dispense R = Recirculation
X	Gasket materials K = DuPont Kalrez®, Compound 6375 Q = FFKM F = FKM E = EPDM
XX	Material Head PE, CD, PF (= PVDF)
XXX	Chemical code Code according table „ chemical coding “ ex: 000 uncoded
X	Orientation fluid port H = Horizontal V = Vertical
X/X	Fluid port 1/4 = 1/4" Flare 3/8 = 3/8" Flare 1/2 = 1/2" Flare 3/4 = 1/4" Flare 1 = 1" Flare
X	Orientation venting port H = Horizontal V = Vertical
X/X	Venting port 1/4 = 1/4" Flare 3/8 = 3/8" Flare 1/2 = 1/2" Flare

Example: DH-DK-PE-001-VF3/4-VF3/8

